

Xiamen Rizheng Industry Co.,Ltd

Peace Caritas Pen Kits Assembly Instructions


Required Accessories

- 7mm pen mandrel
- 3 piece Bushing Set RZ-BP249#-BU
- Drill Bit 3/8" RZ-DB3/8
- Barrel Trimmer use 3/8" Shaft
- Live Tailstock Center
- Glue (Thick CA or Epoxy)
- Pen Blank: Minimum Size- 3/4" x 3-1/2"



Preparing the Blank

- Cut 2 blanks to the length of the tube(s) and add 1/16" for squaring off.
- Drill 3/8" holes lengthwise through the blanks.
- Spread glue over the tube(s), insert the blank with a twisting motion to spread the glue evenly inside.
- Center the tubes lengthwise inside the blanks.
- When the glue is dry, square the ends of the blanks. Use a 3/8" barrel trimmer, or a universal pen blank squaring jig with a power disc sander. Take the excess material down flush with the ends of the brass tube. (do not trim beyond the length of the tube since this may interfere with operation of the mechanism and assembly). Use a barrel trimmer to clean the inside of the tube.



Turning the Blank

- Mount the bushings and blanks according to the diagram above.
- Thread on the knurled nut and hand tighten to hold all components in place.
- Slide the tailstock up snugly against the mandrel shaft inserting the live center point into the mandrel dimple, lock in place.
- Hand tighten the quill adjustment to firm up the mandrel. (DO NOT overtighten, it could damage the mandrel).
- Using sharp tools, turn the blank down close to the bushing diameter. Turn the barrel (straight or to a profile of your choice)
- Sand the blank down to be flush with the bushings gradually increasing the sandpaper grits.

- Finish the barrel with your choice of polish. Allow sufficient time for the polish to cure.



Assembly

- Lay out parts according to diagram above.
 - Press the tip into either end of the lower barrel (longer).
 - Press the coupler with center bands into the opposite end of the barrel.
- NOTE: Do not press directly over the threads, instead cut a pen blank to about 3/4" long. Drill a 8mm hole through the blank. Affix the blank over the thread and press the coupler in.
- Affix the spring over the refill end and drop into the opening at the coupler.
 - Screw the twist mechanism over the refill end.
 - Press the clap/clip assembly into the end of the upper barrel(smaller).
 - Press both ends of the pen together to close the gap in the center.
 - The pen operates by twisting the ends to extend or retract the refill.
 - To remove refill-twist off upper cap to expose the refill(Do not pull of cap).